



SMOOTH SURFACE DEPTH SAND FILTERS

QDS



Maximum working pressure:
2.5kg/cm²

- Smooth filter body surface, easy to clean.
- High sand bed.
- UV resistance.
- Effect filtration.
- Outdoor installation allowed.



Depth Sand Filter are manufactured using reinforced polyester with glass fibre, which is completely anticorrosive, with high mechanical, chemical and thermal resistance.

One of its main characteristics is the height of its filtering layer. The higher this is, the better its performance.

Suitable for private and commercial swimming pools.

Specification and size:

Model	Filtration area	Flow	Sand 0.6~1.0mm	Gravel 1~3mm	Valve Size	D	H	B	A	P	C
	(m ²)	(m ³ /h)	(kg)	(kg)	inch	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
QDS13500	0.20	8.0	220	-	1.5	540	1350	75	750	390	125
QDS13650	0.32	12.8	300	-	1.5	650	1350	95	750	565	125
QDS13700	0.38	15.2	420	-	1.5	710	1350	95	750	565	125
QDS15800	0.50	20.0	460	170	2.0	810	1500	150	900	790	220
QDS15900	0.64	25.5	600	226	2.0	910	1500	150	900	790	220
QDS151000	0.79	31.5	740	270	2.0	1010	1500	150	900	790	220

