



STAINLESS STEEL UV STERILIZER

UVF



Split Type Flange Connection UV Disinfection Device

Basic configuration :

1. UV lamp
2. High transmittance quartz tube
3. Electronic Ballast
4. 304/316 stainless steel reactor



5. The electronic control box (time cumulative device, warning indicator) mirrors
 6. Manual / automatic cleaning (optional)
- Sterilization rate: 99.9%
- Sterilization rate: 99.9%

Suitable for pool water, landscape water, cooling water, marine water, desalination, small water flow disinfection and so on.

Specification and size:

Model	Voltage	Working Pressure	Flow	Lamp Configuration	Connection Size	Dimensions
	(V/Hz)	(Mpa)	(m ³ /h)	(W)		(mm)
UVF-240	220/50	0.6	30	120×2	65	1320×195×550
UVF-360	220/50	0.6	40	120×3	80	1320×220×550
UVF-480	220/50	0.6	50	120×4	100	1320×250×650
UVF-600	220/50	0.6	65	120×5	100	1320×250×680
UVF-720	220/50	0.6	75	120×6	100	1320×300×700
UVF-960	220/50	0.6	90	120×8	150	1320×350×750
UVF-1080	220/50	0.6	100	120×9	150	1320×350×750
UVF-1200	220/50	0.6	120	120×10	150	1320×400×800
UVF-1920	220/50	0.6	180	320×6	200	1700×350×750
UVF-2560	220/50	0.6	220	320×8	225	1700×400×800
UVF-3520	220/50	0.6	360	320×11	250	1700×450×850
UVF-4800	220/50	0.6	480	320×15	250	1700×500×900
UVF-6400	220/50	0.6	600	320×20	350	1700×600×1060
UVF-7040	220/50	0.6	660	320×22	350	1700×600×1060