

EREE CHLORINE MULTIFUNCTION CONTROLSYSTEM

AUT-800

Using high quality electronic components and excellent housing material, is a pool water quality intelligent monitoring system, designed to control residential and commercial swimming pool and SPA pool water free chlorine content, PH value and temperature.



Accessories:



16 Words Double Line LCD Display

Specification:

PH measurement-- range: 0~14;

Resolution: ± 0.01

CL measurement -- range: 0-200PPM;

Resolution: ±0.01; Accuracy: 1%

Temperature measurement--

PT100;

Range: 0-100°C; Resolution: 1°C; Accuracy: 1%

Power input -100° 240V, 50 ~ 60Hz

Signal Input -- external trigger (flow meter) input

 $(15 \sim 30 \text{Vac} / \text{Vdc})$

Output $-0/4 \sim 20 \text{mA}$, 4 dosing pump relay output

(10A, 220V)

Power -- 15W

Dimensions --300 (H) \times 290 (W) \times 143 (D)mm

Installation -- wall-mounting

Working environment --

Temperature: $0 \sim 40^{\circ}\text{C}$;

Relative Humidity: $0 \sim 95\%$ (non-condensing)

Weight -- 2.45kg

Housing material -- ABS

Protection degree -- IP65